


LEAD FINISH: SILVER	
BUSHING FINISH: SILVER	
CAPACITANCE	5500pF GMV
TEMP. RANGE	-55°C TO 125°C
CURRENT	3 AMP MAX.
WORKING VOLTAGE	85°C -- VDC MAX. 125°C 100 VDC MAX.
D.C. RESISTANCE	0.1ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	

FREQ. MHZ	I.L. (db)
3	7
10	14
30	40
100	60
300	70
1 GHz	70



MARKING:

PART: S729305

BAG:
 51-729-305
 DATE CODE
 QTY./BAG (50 MAX.)

	30	29	28	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED
	CN 201370	CN 190123	CN. 184953 REDRAWN	CHANGE NOTICE	Fractions ± 1/64
					Dec. .xx±
					Dec. .xxx±.005
					Angles ±0° 30'
					CODE IDENT. NO. DLSP2

ERIE, FAIRVIEW
 PENNSYLVANIA

SPECTRUM CONTROL INC.

Dwn. KAUFFMAN	Description Pi
Ckd. 4/25/01	RESIN SEAL FILTER
Apvd.	51-729-305
Scale NONE	